

General Disclaimer

One or more of the Following Statements may affect this Document

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

SE AU



NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

NASA Program Apollo Working Paper No. 1338

INVESTIGATION OF THE DIVING CHARACTERISTICS OF THE
APOLLO COMMAND MODULE DURING WATER LANDINGS



FACILITY FORM 602

N70 - 35863

(ACCESSION NUMBER)


(THRU)

13
(PAGES)

(CODE)

TMX-64442
(NASA CR OR TMX OR AD NUMBER)

31
(CATEGORY)




MANNED SPACECRAFT CENTER
HOUSTON, TEXAS

May 22, 1968

NASA PROGRAM APOLLO WORKING PAPER NO. 1338

INVESTIGATION OF THE DIVING CHARACTERISTICS OF THE
APOLLO COMMAND MODULE DURING WATER LANDINGS

PREPARED BY



Bruce M. Wood
AST, Recovery Systems Branch

AUTHORIZED FOR DISTRIBUTION



Christopher C. Kraft, Jr.
Director of Flight Operations

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION
MANNED SPACECRAFT CENTER
HOUSTON, TEXAS
May 22, 1968

CONTENTS

Section	Page
SUMMARY	1
INTRODUCTION	1
APPARATUS AND PROCEDURE	2
RESULTS AND DISCUSSION	2
CONCLUSIONS	3

TABLES

Table		Page
I	SCALE RELATIONSHIPS	4
II	TEST PARAMETERS AND SPACECRAFT DATA	5

FIGURES

Figure		Page
1	Pendulum apparatus, model, and test tank	6
2	Apollo CM (1/7-scale) water penetration test series 1 data	7
3	Apollo CM (1/7-scale) water penetration test series 2 data	8
4	Typical velocity curves — test series 1	9
5	Typical sequences	
	(a) Drop resulting in a stable II attitude	10
	(b) Drop resulting in a stable I attitude	10

INVESTIGATION OF THE DIVING CHARACTERISTICS OF THE APOLLO COMMAND MODULE DURING WATER LANDING

By Bruce M. Wood

SUMMARY

Tests were conducted to investigate the diving characteristics of the Apollo command module during water landings using a 1/7-scale model. For all landings investigated, the model was released into calm water. Vertical and horizontal velocities were varied to simulate two- and three-parachute landings, and wind drift, respectively. Roll and pitch attitude were also varied to represent the launch-abort conditions and parachute oscillation. The test results indicate that the Apollo command module may be expected to penetrate water to depths of at least 8 to 12 feet, with an occasional plunge to depths of 14 to 17 feet under worst-case conditions. In all tests, the underwater velocity decreased rapidly to 5 to 10 ft/sec prior to the command module reaching a depth of 8 feet.

INTRODUCTION

This paper presents the results of two test programs conducted in the water test-tank facility located in building 260 at the Manned Spacecraft Center. The primary purpose of the tests was to determine the underwater velocity profile and maximum dive depths that an Apollo command module would exhibit during a landing after a launch abort. The maximum dive depth data were required to analyze the launch site landing area at Kennedy Space Center to determine locations of shallow-water areas in which possible command module damage due to bottom contact might occur. A landing in such an area could result in incapacitation of members of the flightcrew as well as rupture of the pressure vessel. The latter condition could cause the spacecraft to assume an attitude dangerous to the crew or one from which it would be impossible for the crew to escape. The purpose of this paper is to provide data for recovery planners that can be used in conjunction with other information such as results of spacecraft structural tests, information on underwater bottom characteristics in the launch site area, and launch abort trajectory analyses.

APPARATUS AND PROCEDURE

A 1/7-scale model of the Apollo command module was used to conduct the tests. The model consisted of a hollow body of revolution with an outside shell constructed of fiber glass. A removable upper deck with simulated equipment was bolted to the vehicle. A three-axis balance system with lead weights inside the model was used to achieve the proper center of gravity and moments of inertia. The bifilar-pendulum method was used to determine the scaled moments of inertia. Scale relationships are given in table I.

The water-landing penetration investigation was conducted by launching the model as a free body using a pendulum apparatus (fig. 1). A predetermined free-fall height was used to obtain the desired vertical velocity component. The horizontal velocity was achieved by pulling the pendulum up to a predetermined height as shown in figure 1. The model was released electrically from the pendulum while at the vertical position of the swing using a solenoid and cam-operated switch. Each drop was recorded on film at 120 frames per second with a motion picture camera located at the waterline. The film was analyzed using a single-frame film viewer which provided accurate measurement of time and displacement with reference to the surface of the water.

RESULTS AND DISCUSSION

A summary of the test conditions is given in table II. These conditions represent the variables associated with a landing after a launch abort. Both the two-parachute and the nominal three-parachute landing modes were investigated.

All tests results are presented in figures 2, 3, and 4. These plots show the effect of the various test variables on the depth of dive for the Apollo command module. Shown in figure 4 are plots of dive depth versus velocity. These curves represent typical underwater velocities of the lowest point on the spacecraft. They were generated by plotting the underwater position of the model with respect to time and differentiating the resulting curve.

The majority of the test results indicate that the Apollo command module will penetrate the water at least 8 to 12 feet, and occasionally 14 to 17 feet. The deepest water penetration appears to result from a high-pitch, 180-degree roll, with a moderate-wind condition. From observations made of the impact behavior of the model during the test drops, it appears that higher wind velocities will result in less water penetration since the model tends to dish out, or tumble, rather than dive.

The tumbling of the model results in a greater possibility of its assuming a Stable II flotation attitude (apex-down). (Test drops resulting in a Stable II attitude are labeled "II" on the plotted data.) A side effect of underwater tumbling is the possibility of the upper deck striking bottom. This condition was observed on several drops. Figure 5 shows two typical drops that were recorded by the camera.

CONCLUSIONS

For analysis purposes, a penetration depth of at least 17 feet must be considered as a possibility for bottom contact with a two-parachute landing configuration. Also to be considered is that almost any underwater attitude may result from various combinations of wind, oscillation, roll, and pitch.

Using the probable dive depths of the Apollo command module and the corresponding velocity profiles, hydrostatic and dynamic pressures may be calculated. Also, underwater impact velocities for use in structural failure analyses and launch-area abort recovery planning may be predicted.

TABLE I.- SCALE RELATIONSHIPS

[S = Scale of model]

Quantity	Full size	Scale factor	Model
Length	L	S	SL
Area	A	S^2	S^2A
Weight	W	S^3	S^3W
Moment of inertia	I	S^5	S^5I
Time	T	\sqrt{S}	$\sqrt{S} T$
Speed	V	\sqrt{S}	$\sqrt{S} V$
Linear acceleration	a	1	a
Angular acceleration	α	S^{-1}	$S^{-1}\alpha$

TABLE II.- TEST PARAMETERS AND SPACECRAFT DATA

[Full-scale]

Test 1	Test 2
Weight, lb 10 000	Weight, lb 11 344
Center of gravity, in. X = 35.7	Center of gravity, in. X = 37.7
Y = 0.7	Y = 0
Z = 4.4	Z = 4.3
Two-parachute landing	
Vertical velocity, ft/sec 33	Vertical velocity, ft/sec 37
Oscillation, deg ± 8	Oscillation, deg ± 8
Wind, ft/sec 0, 15, 30	Wind, ft/sec 20, 30
Roll, deg 0, 90, 180	Roll, deg 90, 135, 180
Three-parachute landing	
Vertical velocity, ft/sec 27	Vertical velocity, ft/sec 29
Oscillation, deg ± 6	Oscillation, deg ± 4
Wind, ft/sec 0, 15, 30	Wind, ft/sec 20, 30
Roll, deg 0, 90, 180	Roll, deg 90, 135, 180




Figure 1.- Pendulum apparatus, model, and test tank.

Symbol Π indicates an apex down flotation attitude






Figure 2.- Apollo CM (1/7-scale) water penetration test series 1 data.

Symb: I II indicates an apex down flotation attitude




(a) Vertical velocity = 29 ft/sec.




(b) Vertical velocity = 37 ft/sec.

Figure 3.- Apollo CM (1/7-scale) water penetration test series 2 data.



(a) Vertical velocity = 27 ft/sec.



(b) Vertical velocity = 33 ft/sec.

Figure 4.- Typical velocity curves — test series 1.





Figure 5.- Typical sequences.